


### AUX R32 - The Free Match Inverter Series - AFEB09HP230V1FL

Job Name \_\_\_\_\_ Location \_\_\_\_\_ Date \_\_\_\_\_  
 Purchaser \_\_\_\_\_ Engineer \_\_\_\_\_  
 For  Reference  Approval   
 Submitted to \_\_\_\_\_ Construction \_\_\_\_\_  
 Unit Designation \_\_\_\_\_ Schedule # \_\_\_\_\_



- ❖ Fresh air intake
- ❖ Anti-condensation
- ❖ Low noise
- ❖ Two-way drainage
- ❖ Filter
- ❖ Easy to disassemble

Indoor Unit		AFEB09HP230V1FL	
Capacity	Cooling	Btu/h	9000
	Heating	Btu/h	11000
Electric Data	Power Supply	V~Hz/Ph	208~230,60,1
	Input Current	A	0.3
Indoor Unit	Air Flow Rate (Tu/Hi/Mi/Lo)	CFM	500/459/382/324
	Sound Pressure Level	dB(A)	39
	Net Dimensions	inch	39.37×27.17×9.25
		mm	1000×690×235
	Packing Dimension (Panel)	inch	42.52×30.32×12.80
		mm	1080×770×325
Net/Gross(body)	lbs	57.3/67.2	
Piping Diameter	Liquid Side	In.[mm]	1/4[6.35]
	Gas Side	In.[mm]	3/8[9.52]

### Remarks:

- 1.All specifications are subject to change by the manufacturer without prior notice.
- 2.All units are being tested and comply to ISO5151.
- 3.Sound pressure levels are measured in anechoic chamber.  
 During actual operation, sound pressure level will be higher as a result of room specification condition.
- 4.Data from AUX lab,08/03/24, Data may change according to test surroundings, AUX reserves right of explanation on data.



## Dimensions

Indoor Unit

AFE09HP230V1FL

