

AUX R32 - The Free Match Inverter Series - AFEB18HP230V1SD

Job Name _____ Location _____ Date _____
 Purchaser _____ Engineer _____
 For Reference Approval
 Submitted to _____ Construction _____
 Unit Designation _____ Schedule # _____



- ❖ Flexible air intake
- ❖ Fresh air intake
- ❖ Two-way drainage
- ❖ Larger static pressure range
- ❖ Removable control box
- ❖ Constant air volume

Indoor Unit		AFEB18HP230V1SD	
Capacity	Cooling	Btu/h	18000
	Heating	Btu/h	19000
Electric Data	Power Supply	V~Hz/Ph	208~230,60,1
	Input Current	A	0.6
Indoor Unit	Air Flow Rate (Tu/Hi/Mi/Lo)	CFM	530/488/412/344
	Sound Pressure Level	dB(A)	39
	Static Pressure	in.w.g	0.1(0~0.32)
	Net Dimensions	inch	27.56×27.56×9.65
		mm	700×700×245
	Package Dimensions	inch	36.61×32.68×11.81
mm		930×830×300	
Net/Gross(body)	lbs	47.4/56.2	
Piping Diameter	Liquid Side	In.[mm]	1/4[6.35]
	Gas Side	In.[mm]	1/2[12.7]

Remarks:

- 1.All specifications are subject to change by the manufacturer without prior notice.
- 2.All units are being tested and comply to ISO5151.
- 3.Sound pressure levels are measured in anechoic chamber.
 During actual operation, sound pressure level will be higher as a result of room specification condition.
- 4.Data from AUX lab,08/03/24, Data may change according to test surroundings, AUX reserves right of explanation on data.





Dimensions

Indoor Unit

AFE18HP230V1SD

